

MODEL P200



SPECIFICATIONS

Description:

Rack mount or freestanding surround sound processor

Key Features:

RoomPerfect™, capable of handling up to 256 output channels, HDCP 2.2, 4K resolution, video scaling, 3D video, advanced HDMI™ switching, video tiling and split screen display processing, Dolby Atmos, DTS:X, AURO-3D®

Decoding:

Dolby® Atmos, Dolby Digital, Dolby Digital EX, Dolby Digital Plus, Dolby TrueHD, DTS, DTS ES Discrete 6.1, DTS ES Matrix 6.1, DTS 96/24, DTS-HD High Resolution Audio, DTS-HD Master Audio, AURO-3D®, 12 channels

Post processing:

Dolby surround, AURO-MATIC®, Dolby Pro Logic II, Dolby Pro Logic IIx, , Dolby Pro Logic IIz, Dolby EX, DTS Neo:6, DTS NEO:X

Input:

Audio: 1 x AES/EBU S/P-DIF input, 3 x S/P-DIF coaxial inputs, 4 x S/P-DIF optical inputs, 1 x USB audio input (≤192kHz/32bit), 1 x balanced stereo analog input (XLR), 4 x single ended stereo analog inputs (RCA), 1 x multichannel single ended analog input (RCA), 1 x microphone input (XLR)

Video: 8 x HDMI™

Output:

Audio: 5 x Steinway Lyngdorf Digital Links (CAT 5e based), 1 x single ended stereo analog output for secondary audio output, 1 x SPDIF coax digital output, 5 x HDMI™

Video: 4 x HDMI™ – ARC compatible, use 4 screens as one coherent display, show 4 inputs on one HDMI output, picture in picture, 1 x HDBaseT connector – show 4 inputs on one output, picture in picture

Miscellaneous:

1 x DB9 RS232 connector, 2 x IR sensor inputs, 1 x IR output (loop from one of the sensor inputs), 1 x Trigger input, 4 x Trigger outputs, 1 x RJ45 Ethernet LAN connector, 2 x USB connectors, 1 x SD card slot (Storage for system software)

Interface Options:

RS232, IP, Web Interface, ihiji, Remote Control App on iOS and Android platforms

Dimensions (H x W x D):

14.0 x 45.0 x 35.9 cm

5.51 x 17.7 x 14.1 in